

## PREMIER PANEL FASTENERS

Premier Building Systems has completed the development of a panel fastener. This fastener was developed specifically, for the attachment of Premier panels to beams, purlins and posts made of wood and soft iron. Premier's Panel fastener uses state of the art tempering and coating technology to create a #15 screw that drives easily into hard woods, engineered woods and soft steel without bending, breaking or stripping out the multi-lobed head. The screw is corrosion resist and passes more than 15 cycles in the industry standard "Kesternich cabinet".

The screw has been designed with an aggressive thread pattern that demonstrates excellent pull out resistance. In independent code recognized laboratory testing, Premier Panel fasteners exhibited 980 pounds of pull-out resistance when installed 1" into a typical SPF#2 2 x 4. The laboratory also checked the screw for resistance to shear. The test was designed to simulate a worse case scenario where a 14" Premier Panel fastener was driven through a 12" thick panel and into SPF#2 dimensional lumber. The fastener withstood over 830 pounds of force without shearing. The failure mode was the screw pulling through the OSB.

The use of the Premier Panel fastener is specified in the Premier Panel Details Book. Wall connections require that screws be utilized 2' on center. The frequency of panel fasteners required to anchor roof panels is dependent on the imposed loads the panels must resist and the number of attachment points available. See the Premier Panel Details Book for recommendations and follow the requirements specified on the shop drawings.

The Premier Panel fastener can be used in light gauge steel framing up to 1/4" thick. Different points are used on the Premier Panel fasteners that are used in these light gauge steel applications, so you will want to check with your Premier Building System representative for the requirements of your specific project.